










MANTEL SMT-4510

Mineralized filter.activator for H²O molecules

Flow-rate 300-450 Litre/hr.

Dimension : 150W-400L-400H

NO	FILTER	DESCRIPTION
1.		Sediment filter, Material : polypropylene, micron rating :5um Pressure drop:0.04 bar@20l/min,mix.op.temp: 60 C° Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.
2.		Resin filter, kastel cl300 Pressure drop:0.05 bar@5l/min,mix.op.temp: 60 C° Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.
3.		carbon block filter, Material: coconut shell ,micron rating :10um Pressure drop:0.05 bar@5l/min,mix.op.temp: 60 C° Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.
4.		Post carbon filter, activate inline , mix.op.temp: 50 C°,max flow=0.75 gpm,service life=2,500gall Max op. pressure :125 psi, dimension: 63mm.
5.		Mineralized filter activator for H ² O molecules mix.op.temp: 42 C°,max flow=0.75 gpm,service life=2,500 gall Max op. pressure :125 psi, dimension: 50mm.
6.		Gooseneck faucet and shut-off-valve ,tube Ø¼ inch
7.		Filter wrench.